





**A SALDARE  
TO WELD  
A SOUDER  
PARA SOLDAR**



**FILETTATO  
THREADED  
FILETE'  
ROSCADO**



**Polietilene S5 — EN 1555  
HDPE S5  
Acciaio — UNI 10208  
Steel**

**UNI 9736**




**IT VERSIONE  
A SALDARE**

**EN WELD  
VERSION**

**FR VERSION  
A SOUDER**

**ES VERSIÓN  
S/S**

			kg pz kg piece
25 mm x 3/4"	20150	24	0,6
32 mm x 1"	20151	15	1
40 mm x 1 1/4"	20152	12	1,2
50 mm x 1 1/2"	20153	8	2,1
63 mm x 2"	20154	6	3,3
75 mm x 2 1/2"	20155	4	4
90 mm x 3"	20156	3	6,5
110 mm x 4"	20157	2	6,7
125 mm x 4"	20158	1	6,9
140 mm x 5"	20165	1	12,1
160 mm x 6"	20159	1	18,6
*180 mm x 6"	20160	1	20
*200 mm x 8"	20161	1	27,9
*225 mm x 8"	20162	1	29,9



\* Prodotti non zincati. Si forniscono su richiesta giunti con diametro maggiore.

\* Produits non zingués. Sur demande raccord de transition avec diamètres différents.

\* Not galvanized products. Fittings with bigger diameter on request.

\* Productos no galvanizados. A petición son disponibles las juntas con diferentes diámetros.

**IT VERSIONE  
FILETTATA**

**EN THREADED  
VERSION**

**FR VERSION  
FILETE'**

**ES VERSIÓN  
ROSCADA**

D1	D2	L	L1	L2	S1	S2
3/4"	25	450	150	300	2,3	3,0
1"	32	450	150	300	2,6	3,0
1 1/4"	40	450	150	300	2,6	3,7
1 1/2"	50	450	150	300	2,9	4,6
2"	63	450	150	300	2,9	5,8
2 1/2"	75	500	200	300	3,2	6,8
3"	90	500	200	300	3,2	8,2
4"	110	500	200	300	3,6	10,0
4"	125	500	200	300	3,6	11,4
5"	140	550	250	300	5,0	12,7
6"	160	600	250	350	5,0	14,6
6"	180	600	250	350	5,0	16,4
8"	200	700	300	400	5,6	18,2
8"	225	700	300	400	5,6	20,5

			kg pz kg piece
25 mm x 3/4"	20210	24	0,6
32 mm x 1"	20211	15	1
40 mm x 1 1/4"	20212	12	1,2
50 mm x 1 1/2"	20213	8	2,1
63 mm x 2"	20214	6	3,3
75 mm x 2 1/2"	20215	4	4
90 mm x 3"	20216	3	6,5
110 mm x 4"	20217	2	6,7
125 mm x 4"	20218	2	6,9

La parte zincata deve essere protetta dalla corrosione prima dell'interramento mediante l'applicazione di bande catramate a freddo o nastri isolanti specifici.

La partie galvanisée doit être protégée contre la corrosion avant d'être enterrée avec une bande goudronnée à froid ou une bande isolante spécifique.

The galvanized part must be protect from the corrosion before the interment through the application of tar bandages without heating or specific insulating tapes.

La parte galvanizada debe ser protegida contra la corrosión antes del enterramiento a través de la aplicación de vendaje de alquitrán o cintas aislantes específicas.

i valori di L, L1 e L2 sono valori minimi  
L, L1 and L2 are the minimum value available  
Les valeurs L1 et L2 sont valeurs minimums  
los valores de L, L1 y L2 son valores minimos